

MATERIAL SAFETY DATA SHEET



IDENTITY COATED ABRASIVES "SILICON CARBIDE"	TRADE NAME A-99 , C-99 , B-99 , & Q99
--	--

SECTION I (MATERIAL IDENTIFICATION)

MANUFACTURER'S NAME Fábrica Nacional de Lija, S.A de C.V.	EMERGENCY TELEPHONE NUMBER 011 525 3661403
ADDRESS (Street, Number, City, State, ZIP Code) Av. Presidente Juárez # 225 San Jerónimo Tepetlaco Tlalnepantla 54000 Estado de México MEXICO	TELEPHONE & FAX NUMBER FOR INFORMATION 011 525 366 1400 fax 011 525 366 1499
	REVISION DATE July, 2006
	PREPARED BY (Technical contact) Alfredo Bafiuelos or José Jiménez

SECTION II (MATERIAL DESCRIPTION & HAZARD RATING)

TECHNICAL DESCRIPTION: Silicon Carbide coated on a paper backing and resin binder.	HAZARD RATING: 1, 0, 0	NFPA CODE
CHEMICAL FAMILY NA		Blue: Health hazard Red: Fire hazard Yellow: Reactivity hazard White: Special hazard 0: Minimum 1: Slight 2: Moderate 3: Serious 4: Extreme
CHEMICAL NAME/FORMULA NA		
SYNONYMOUS NA		

SECTION III (HAZARDOUS INGREDIENTS/IDENTITY INFORMATION)

Chemical name	CAS No.	Common name (s)	Percent	OSHA - PEL (mg/m ³)	ACGIH-TLV (mg/m ³)
Silicon Carbide (SiC)	409 - 21 - 2	Silicon Carbide	12 - 55	15.0 (total dust)	10.0 (total dust)
Epoxy and Phenol-Formaldehyde resin "cured"	NONE	epoxy and phenolic resin	10 - 25	-----	-----
Paper backing	NONE	-----	25 - 70	-----	-----

REMARKS
 The above materials are not carcinogen.
 Materials are regulated by OSHA 29 CFR 1910.1200, Hazard Communication and/or The Massachusetts General Law, Chapter III, Right to know Regulations

SECTION IV (PHYSICAL & CHEMICAL CHARACTERISTICS)

BOILING POINT NA	SOLUBILITY IN WATER NA	SPECIFIC GRAVITY (H₂O=1) NA
VAPOR PRESSURE NA	SOLUBILITY IN ALCOHOL NA	MELTING POINT NA
VAPOR DENSITY (Air = 1) NA	SOLUBILITY IN OTHER SOLVENT NA	% VOLATILE BY VOLUME NA
APPEARANCE & ODOR	Paper coated with abrasive particles which are bonded with resin binder.	EVAPORATION RATE NA

SECTION V (FIRE & EXPLOSION HAZARD DATA)

FLASH POINT (Method used) NA	FLAMMABLE LIMITS	LEL NA	UEL NA
--	-------------------------	------------------	------------------

EXTINGUISHED MEDIA
 Water, carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES
 Backings and cured resin will burn or decompose.
 Use respiratory protection.

UNUSUAL FIRE & EXPLOSION HAZARDS
 NA

MATERIAL SAFETY DATA SHEET



IDENTITY COATED ABRASIVES "SILICON CARBIDE"	TRADE NAME A-99 , C-99 , B-99 , & Q99
--	--

SECTION VI (REACTIVITY DATA)

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	NA
INCOMPATIBILITY (Materials to Avoid) In use organic fumes may be liberated.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	NA

SECTION VII (HEALTH HAZARD DATA)

ROUTE (s) OF ENTRY	INHALATION	SKIN	INGESTION
During use	Airborne dusts or fumes.	Airborne dusts or fumes.	Airborne dusts or fumes.
HEALTH HAZARDS (Acute & chronic) ACUTE & CHRONIC: Breathing difficulty, skin, eye, nasal and respiratory irritation.			
CARCINOGENICITY	NTP	IARC MONOGRAPHS	OSHA REGULATED
	NA	NA	NA
SIGNS & SYMPTOMS OF EXPOSURE Deposits or material on skin, in eyes and nasal passages. Coughing and/or breathing difficulties may be present.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pulmonary disorders, skin or eye disorders.			
EMERGENCY & FIRST AID PROCEDURES Remove to dust free area. Irrigate eyes and/or skin with copious amounts of water. SEEK MEDICAL ATTENTION.			

SECTION VIII (PRECAUTIONS FOR SAFE HANDLING & USE)

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Ordinary precautions for dust and particulates.
WASTE DISPOSAL METHOD In compliance with Federal, State and local regulations for landfill.
PRECAUTIONS TO BE TAKEN IN HANDLING & STORING Not applicable
OTHER PRECAUTIONS Not applicable

SECTION IX (CONTROL MEASURES)

RESPIRATORY PROTECTION (Specify type)		If limits are exceeded during sanding or grinding, an approved NIOSH respirator must be used. OSHA 29 CFR 1910 - 134	
VENTILATION	LOCAL EXHAUST Must be used to control exposure to dust or fumes.	SPECIAL	NA
	MECHANICAL (General) Hoods connected to exhaust ducts and appropriate dust collector.		
PROTECTIVE GLOVES abrasion and/or skin irritation.	Wear gloves to prevent	EYE PROTECTION	Wear safety glasses while sanding or grinding. OSHA 29 CFR 1910 . 133
OTHER PROTECTIVE CLOTHING OR EQUIPMENT Hearing protection OSHA 29 CFR 1910 . 215			
WORK/HYGIENIC PRACTICES Ordinary washing and cleanliness practices.			

ABBREVIATIONS: NA = NOT APPLICABLE

"THE INFORMATION IS PROVIDED IN GOOD FAITH AND IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, FABRICA NACIONAL DE LIJA, S.A de C.V. MAKES NO WARRANTY WITH RESPECT OF THE ACCURACY OF THE INFORMATION AND DISCLAIMS RESPONSIBILITY FOR DAMAGES OF ANY KIND RESULTING FROM THE USE OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. CUSTOMERS ARE ENCOURAGED TO MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THIS PRODUCT FOR THEIR PURPOSE PRIOR TO USE".