MATERIAL SAFETY DATA SHEET



				Coa	ated Abrasives		
IDENTITY			TRADE NAME				
COATED ABRA	SIVES "ALUMINU	IM OXIDE"	E-088				
SECTION I (MATERIAL IDE			11.				
SECTION I (MATERIAL IDE	MIFICATION)						
MANUFACTURER'S NAME			EMERGENCY TELEF	PHONE NUMBER			
Fábrica Nacional de Lija, S.A de C.V.			011 525 366 1403				
ADDRESS (Street, Number, City, State, ZIP Code)			TELEPHONE & FAX NUMBER FOR INFORMATION				
Av. Presidente Juárez # 225			011 525 366 1400 fax 011 525 366 1499				
San Jerónimo Tepetlacalco			REVISION DATE				
Tlalnepantla 54000 Estado de México			July, 2006 PREPARED BY (Technical contact)				
MEXICO			Alfredo Bañuelos or José Jiménez				
			Pair edo Barideios or	Jose Jimenez			
SECTION II (MATERIAL DE	SCRIPTION & HAZARI	D RATING)					
TECHNICAL DESCRIPTION		oated on a paper	HAZARD RATING:	I, 0, 0	NFPA CODE		
	cking and resin binder.						
CHEMICAL FAMILY	NIA		0	Blue: Health hazard Red: Fire hazard	0: Minimum		
CHEMICAL NAME/FORMUL	NA A			Yellow: Reactivity hazard	1: Slight 2: Moderate		
STELLIONE TO THE TOTAL TO THE	NA NA		0	White: Special hazard	3: Serious		
SYNONYMOUS					4: Extreme		
	NA						
			·				
SECTION III (HAZARDOUS	INGREDIENTS/IDENT	TITY INFORMATION)					
HAZARDOUS COMPONEN	TS						
Chemical name	CAS No.	Common name (s)	Percent	OSHA - PEL (mg/m3)	ACGIH-TLV (mg/m3)		
Aluminum Oxide (Al2O3)	1344 - 28 - 1	Alpha Alumina	15 - 55	15.0 (total dust)	10.0 (total dust)		
Phenol-Formaldehyde	NONE	Phenolic Resin	15 - 35				
resin "cured"							
Paper backing	NONE		25 - 65				
raper backing	NONE		23 - 63				
REMARKS		•	•	II.			
The above materials are not card	inogen.						
Materials are regulated by OSHA	29 CFR 1910.1200, Hazaro	d Communication and/or The Mass	achusetts General Law, C	Chapter III, Right to know Regula	ations		
SECTION IV (PHYSICAL & C	CHEMICAL CHARACT	ERISTICS)					
BOILING POINT	NA	SOLUBILITY IN WATER	NA	SPECIFIC GRAVITY (H2C)=I) NA		
VAPOR PRESSURE	NA	SOLUBILITY IN ALCOHOL	NA	MELTING POINT	NA		
VAPOR DENSITY (Air = I) NA APPEARANCE & ODOR		SOLUBILITY IN OTHER SOLVENT NA		% VOLATILE BY VOLUME NA			
		Paper coated with abrasive particles which are		EVAPORATION RATE NA			
		bonded with resin binder.					
SECTION V (FIRE & EXPLO	SION HAZARD DATA)					
FLASH POINT (Method used)		FLAMMABLE LIMITS		LEL	UEL		
NA				NA	NA		
EXTINGUISHED MEDIA		•		•			
	Water, carbon dioxide, Di	ry chemical, Foam					
SPECIAL FIRE FIGHTING PI							
Backings and cured resin will burn or decompose.							
	Use respiratory protection	l.					
UNUSUAL FIRE & EXPLOSI	ON HAZARDS						

NA

MATERIAL SAFETY DATA SHEET



IDENTITY			TRADE NAME							
COATED ABRASIVES "ALUMINUM OXIDE"			E-088							
SECTION VI (REACTIVITY DATA)										
STABILITY	UNSTABLE		CONDITIONS TO AVOID							
O PADILITY	STABLE	X		NA						
INCOMPATIBILITY (Materials to Avoid)										
In use organic fumes may be liberated.										
HAZARDOUS DECOMPOSITION OR BY PRODUCTS										
HAZARDOUS	MAY OCCUR		CONDITIONS TO AVOID							
POLYMERIZATION	WILL NOT OCCUR	X	NA							
SECTION VII (HEALTH HAZARD DATA)										
ROUTE (s) OF ENTRY		INHALATI	ION SKIN		INGESTION					
During use	` '		Airborne dusts or fumes.		Airborne dusts or fumes.					
HEALTH HAZARDS (Acute	& chronic)	ACUTE & CHRONIC: Breathing of	difficulty, skin, eye, nasal ar	nd respiratory irritation.						
The second of th										
CARCINOGENICITY		NTP	IARC MC	ONOGRAPHS	OSHA REGULATED					
		NA		NA	NA					
SIGNS & SYMPTOMS OF EX	EXPOSURE Deposits or material on skin, in eyes and nasal passages. Coughing and/or breathing difficulties may be present.									
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pulmonary disorders, skin or eye disorders.										
EMERGENCY & FIRST AID PROCEDURES										
Remove to dust free area. Irrigate	e eyes and/or skin with copi	ous amounts of water.								
SEEK MEDICAL ATTENTION.										
SECTION VIII (PRECAUTIONS FOR SAFE HANDLING & USE)										
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED										
Ordinary precautions for dust and particulates.										
WASTE DISPOSAL METHOD										
In compliance with Federal, State and local regulations for landfill.										
PRECAUTIONS TO BE TAKEN IN HANDLING & STORING										
Not applicable										
OTHER PRECAUTIONS										
Not applicable										
SECTION IX (CONTROL MEASURES)										
RESPIRATORY PROTECTION (Specify type) If limits are exceeded during sanding or grinding, an approved NIOSH repirator must be used. OSHA 29 CRF 1910 - 134										
VENTILATION	LOCAL EXHAUST Must be used to control exposure to du		ist or fumes.	SPECIAL	NA					
	MECHANICAL (General) Hoods connected to exhaust ducts		and appropiate dust collector.							
PROTECTIVE GLOVES Wear gloves to prevent EYE PROTECTION Wear safety glasses				Wear safety glasses while sand	ing or grinding.					
abrasion and/or skin irritation.				OSHA 29 CFR 1910 . 133						
OTHER PROTECTIVE CLOTHING OR EQUIPMENT										
Hearing protection OSHA 29 CFR 1910 . 215										
WORK/HYGIENIC PRACTIC										
Ordinary washing and cleanliness practices.										

ABBREVIATIONS: NA = NOT APPLICABLE

"THE INFORMATION IS PROVIDED IN GOOD FAITH AND IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, FABRICA NACIONAL DE LIJA, S.A de C.V. MAKES NO WARRANTY WITH RESPECT OF THE ACCURACY OF THE INFORMATION AND DISCLAIMS RESPONSIBILITY FOR DAMAGES OF ANY KIND RESULTING FROM THE USE OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. CUSTOMERS ARE ENCOURAGED TO MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THIS PRODUCT FOR THEIR PURPOSE PRIOR TO USE".