MATERIAL SAFETY DATA SHEET



				Co	ated Abrasives	
IDENTITY			TRADE NAME			
COATED ABRAS	IVES "SILICON	N CARBIDE"	E-93 , E-96			
SECTION I (MATERIAL IDEN			-1	,		
			L			
MANUFACTURER'S NAME			EMERGENCY TELEPHONE NUMBER			
Fábrica Nacional de Lija, S.A de C.V. ADDRESS (Street, Number, City, State, ZIP Code)			TELEPHONE & FAX NUMBER FOR INFORMATION			
Av. Presidente Juárez # 225	ty, State, ZIF Coul	=)	011 525 366 1400 fax 011 525 366 1499			
San Jerónimo Tepetlacalco			REVISION DATE			
Tlalnepantla 54000			July, 2006			
Estado de México			PREPARED BY (Technical contact)			
MEXICO			Alfredo Bañuelos or José Jiménez			
SECTION II (MATERIAL DESC	RIPTION & HAZA	ARD RATING)				
	Silicon Carbide c	• •	HAZARD RATING:	I, 0, 0	NFPA CODE	
CHEMICAL FAMILY	and resin binde			Blue: Health hazard	0: Minimum	
	NA		0	Red: Fire hazard	I: Slight	
CHEMICAL NAME/FORMULA				Yellow: Reactivity hazard	2: Moderate	
	NA		1 0	White: Special hazard	3: Serious	
SYNONYMOUS	NA				4: Extreme	
SECTION III (HAZARDOUS IN	IGREDIENTS/IDEI	NTITY INFORMATION)				
HAZARDOUS COMPONENTS	5					
Chemical name	CAS No.	Common name (s)	Percent	OSHA - PEL (mg/m3)	ACGIH-TLV (mg/m3)	
Silicon Carbide (SiC)	409 - 21 - 2	Silicon Carbide	10 - 50	15.0 (total dust)	10.0 (total dus	
Organic Glue,Urea-Formaldehyde or Phenol-Formaldehyde resin "cured"	NONE	Animal glue,urea resin and phenolic resin	6 - 35			
Paper backing	NONE		13 - 80			
REMARKS						
The above materials are not carcino Materials are regulated by OSHA 29	J	ard Communication and/or The M	1assachusetts General Law,	Chapter III, Right to know Regi	ulations	
SECTION IV (PHYSICAL & CH	HEMICAL CHARAG	CTERISTICS)				
BOILING POINT	NA	SOLUBILITY IN WATER	NA	SPECIFIC GRAVITY (H2C	D=I) NA	
VAPOR PRESSURE	NA	SOLUBILITY IN ALCOHOL NA		MELTING POINT	NA	
VAPOR DENSITY (Air = I)	NA	SOLUBILITY IN OTHER S		% VOLATILE BY VOLUM		
APPEARANCE & ODOR		Paper coated with abrasive part	icles which are	EVAPORATION RATE	NA	
		bonded with resin binder.				
FLASH POINT (Meti		FLAMMABL	ELIMITS	LEL	UEL	
NA	noa usea)	FLAMMADL	E LIMITS	NA NA	NA NA	
EXTINGUISHED MEDIA	/ater, carbon dioxide,	Dry chamical Foam				
SPECIAL FIRE FIGHTING PRO	CEDURES	·				
	ackings and cured resi se respiratory protect	n will burn or decompose. ion.				
UNUSUAL FIRE & EXPLOSIO	N HAZARDS					
	NA					

CONDITIONS TO AVOID

SECTION VI (REACTIVITY DATA)

STABILITY

UNSTABLE

MATERIAL SAFETY DATA SHEET



IDENTITY			TRADE NAME						
COATED ABRASIVES "SILICON CARBIDE"			E-93 , E-96						
	STABLE	X	NA NA						
INCOMPATIBILITY (Materials to Avoid)									
In use organic fumes may be liberated.									
HAZARDOUS DECOMPOSITION OR BY PRODUCTS									
HAZARDOUS	MAY OCCUR		CONDITIONS TO AVOID						
POLYMERIZATION	WILL NOT OCCUR	X	NA						
SECTION VII (HEALTH HAZARD DATA)									
ROUTE (s) OF ENTRY		INHALAT	NHALATION SK		INGESTION				
During use		Airborne dusts or fumes.	Airborne dusts or fumes. Airborne dust		Airborne dusts or fumes.				
HEALTH HAZARDS (Acute	& chronic)	ACUTE & CHRONIC: Breathing	difficulty, skin, eye, nasal a	nd respiratory irritation.					
,									
CARCINOGENICITY		NTP	IARC MC	ONOGRAPHS	OSHA REGULATED				
	(DOCUME	NA NA		NA III III	NA NA				
SIGNS & SYMPTOMS OF EX	RPOSURE	Deposits or material on skin, in e	eyes and nasal passages. Co	ughing and/or breathing difficu	ilties				
may be present.									
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pulmonary disorders, skin or eye disorders.									
EMERGENCY & FIRST AID I	PROCEDURES								
		pious amounts of water.							
Remove to dust free area. Irrigate eyes and/or skin with copious amounts of water. SEEK MEDICAL ATTENTION.									
SECTION VIII (PRECAUTIONS FOR SAFE HANDLING & USE)									
STEPS TO BE TAKEN IN CA	SE MATERIAL IS REL	EASED OR SPILLED							
Ordinary precautions for dust and particulates.									
WASTE DISPOSAL METHOD									
In compliance with Federal, State and local regulations for landfill.									
PRECAUTIONS TO BE TAKEN IN HANDLING & STORING									
Not applicable									
OTHER PRECAUTIONS									
Not applicable									
SECTION IX (CONTROL MEASURES)									
RESPIRATORY PROTECTION (Specify type) If limits are exceeded during sanding or grinding, an approved NIOSH repirator must be used. OSHA 29 CRF 1910 - 134									
VENTILATION	LOCAL EXHAUST Must be used to control exposure to c		ust or fumes. SPECIAL NA		NA				
	MECHANICAL (General) Hoods connected to exhaust ducts and appropriate dust collector.								
PROTECTIVE GLOVES	ROTECTIVE GLOVES Wear gloves to prevent EYE PROTECTION Wear safety glasses while sanding or grinding.								
abrasion and/or skin irritation.				OSHA 29 CFR 1910 . 133					
OTHER PROTECTIVE CLOTHING OR EQUIPMENT									
Hearing protection OSHA 29 CFR 1910 . 215									
WORK/HYGIENIC PRACTIC	WORK/HYGIENIC PRACTICES								
Ordinary washing and cleanliness practices.									

ABBREVIATIONS: NA = NOT APPLICABLE

"THE INFORMATION IS PROVIDED IN GOOD FAITH AND IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, FABRICA NACIONAL DE LIJA, S.A de C.V. MAKES NO WARRANTY WITH RESPECT OF THE ACCURACY OF THE INFORMATION AND DISCLAIMS RESPONSABILITY FOR DAMAGES OF ANY KIND RESULTING FROM THE USE OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. CUSTOMERS ARE ENCOURAGED TO MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THIS PRODUCT FOR THEIR PURPOSE PRIOR TO USE".